



Motori standard
Standard motors
Standardmotoren

TN IE2



2 poli

2 poles

2 polig



50 Hz

Dati tecnici / Technical Data / Technische Daten


Taglia Size Größe	P _n		n [rpm]	η [%]	cos φ -	I _n [A]	I _{sp} /I _n -	M _n [Nm]	M _{sp} /M _n -	M _{max} /M _n -	J [kgm ²]	kg
	[kW]	[HP]										
80A	0.75	1	2820	77.4	0.80	1.7	4.8	2.5	2.8	2.9	0.00085	8.7
80B	1.1	1.5	2850	79.6	0.84	2.1	6.3	3.7	3.1	3.2	0.00105	10.8
90S	1.5	2	2820	81.3	0.80	3.5	5.9	5	4	3.9	0.00145	12.9
90L	2.2	3	2840	83.2	0.81	4.7	6.2	7.5	4.2	4.4	0.00191	14.8
100A	3	4	2840	84.6	0.84	6.2	7	10.1	4	4.5	0.00347	23.4
112A	4	5.5	2890	85.8	0.81	8.3	7	13.2	3.7	3.6	0.00520	29
112B	5.5	7.5	2900	87	0.82	11.5	7	18	2	2.8	0.00700	33
112C	7.5	10	2880	88.1	0.84	15	7	24.8	2	2.1	0.00750	36
132SA	5.5	7.5	2920	87	0.82	11.2	7.5	18	3.9	4	0.01350	46.5
132SB	7.5	10	2920	88.1	0.85	15	8	24.5	4	4.2	0.01570	52.5
132MA	11	15	2940	89.4	0.85	20.6	9	35.7	4.2	4.5	0.01873	65
160MA	11	15	2930	89.4	0.85	22.9	8.6	35.8	3.5	3.8	0.03198	80
160MB	15	20	2930	90.3	0.85	29.5	8.3	48.9	3.6	3.9	0.04221	91
160L	18.5	25	2935	90.9	0.85	34.7	8.3	60.2	3.9	3.7	0.04860	100
180M	22	30	2930	91.3	0.86	40	7	71.7	2.9	2.2	0.07790	125
200LA	30	40	2940	92	0.90	52	6.6	97.5	3	2.2	0.10520	156
200LB	37	50	2940	92.5	0.89	68.6	7	120	3	2.4	0.12080	205

Valori numerici indicativi e non impegnativi / Indicative and non-binding numerical values / Numerische, nicht verbindliche Richtwerte

Disponibili tutte le forme costruttive / All mounting types available / Alle Bauformen verfügbar

Motori standard
Standard motors
Standardmotoren

TN IE2

 disponibile
available
verfügbar


4 poli

4 poles

50 Hz

4 polig


Dati tecnici / Technical Data / Technische Daten


Taglia Size Größe	P _n		n [rpm]	η [%]	cos φ -	I _n [A]	I _{sp} /I _n -	M _n [Nm]	M _{sp} /M _n -	M _{max} /M _n -	J [kgm ²]	
	[kW]	[HP]										
80B	0.75	1	1415	79.6	0.79	2	6	5	2.9	3	0.00260	10.7
90S	1.1	1.5	1430	81.4	0.75	2.6	6.1	7.3	3.5	3.7	0.00300	13.3
90L	1.5	2	1420	82.8	0.73	3.6	6.4	10.1	4	4	0.00380	15
100A	2.2	3	1420	84.3	0.78	5	6.5	14.8	2.9	3.7	0.00550	20.5
100B	3	4	1420	85.5	0.80	6.6	5.8	20.2	3.2	3.3	0.00680	24.5
112A	4	5.5	1440	86.6	0.80	8.9	7	26.5	3.4	3.6	0.00170	30
132SA	5.5	7.5	1440	87.7	0.81	11.7	7	36.5	3.5	3.7	0.02330	46
132MB	7.5	10	1450	88.7	0.80	15.6	7.5	49.4	3.5	3.7	0.03040	56
160M	11	15	1450	89.8	0.79	22	7.3	72.5	3.5	3.7	0.06430	80
160L	15	20	1460	90.6	0.79	31	7	98.1	3.6	3.1	0.08380	98
180M	18.5	25	1460	91.2	0.82	37	6	121	2.5	2.6	0.01310	126
180L	22	30	1470	91.6	0.82	43	6.8	143	2.5	3	0.01410	136
200L	30	40	1465	92.3	0.82	63	6	196	2.5	2.9	0.01510	182

Valori numerici indicativi e non impegnativi / Indicative and non-binding numerical values / Numerische, nicht verbindliche Richtwerte

Disponibili tutte le forme costruttive / All mounting types available / Alle Bauformen verfügbar

Motori standard
Standard motors
Standardmotoren

TN IE2

 disponibile
available
verfügbar


6 poli

6 poles

6 polig

50 Hz


Dati tecnici / Technical Data / Technische Daten

Taglia Size Größe	P _n		n [rpm]	η [%]	cos φ -	I _n [A]	I _{sp} /I _n -	M _n [Nm]	M _{sp} /M _n -	M _{max} /M _n -	J [kgm ²]	kg
	[kW]	[HP]										
90S	0.75	1	930	75.9	0.71	2.4	3.5	7.7	1.8	2	0.00242	12.5
90L	1.1	1.5	920	78.1	0.73	3.4	3.5	11.4	1.8	2	0.00398	14
100A	1.5	2	950	79.8	0.75	4	4	15.1	1.8	2	0.00519	24
112A	2.2	3	940	81.8	0.75	5.4	6	22.3	2.3	2.2	0.00720	34
132SA	3	4	950	83.3	0.76	7.1	5.4	30.1	2.1	2.1	0.01940	44
132MB	4	5.5	960	84.6	0.78	9.1	5.3	39.8	2.4	2.4	0.02688	55
132MC	5.5	7.5	950	86	0.82	13.3	5.3	55.3	2.6	2.6	0.03430	60
160M	7.5	10	950	87.2	0.82	17.1	5	75.4	2	2.3	0.08300	75
160L	11	15	960	88.7	0.82	24.5	5.5	109	2.3	2.5	0.12500	100
180L	15	20	960	89.7	0.82	30	5.2	149	2.3	2.2	0.20000	147
200LA	18.5	25	950	90.4	0.84	37.5	5.2	186	2.1	2.3	0.25000	177

Valori numerici indicativi e non impegnativi / Indicative and non-binding numerical values / Numerische, nicht verbindliche Richtwerte

Disponibili tutte le forme costruttive / All mounting types available / Alle Bauformen verfügbar